

CLASS 1

Building Product Information Sheet

Product name:

Kinetic - Black EPDM Rooftiles

Product description and its intended use:

Kinetic Square roof flashing for sealing around pipes protruding through steel sheet roof, made from EPDM Rubber with aluminum base for molding to the surface.

Product identifier *(if applicable):*

Kinetic - Black EPDM Rooftiles

(This could be a Global Trade Item Number (GTIN) or quick response code (QR code), or any other distinguishable part/model number or identifier.)

Place of manufacture: Aotearoa New Zealand Overseas

Legal and trading name of the manufacturer(s):

Kinetic Sourcing Group Pty Ltd

Address for service:

Level TREET NAME 15/3 Box Road, SUBURB Caringbah

CITY, COUNTRY Sydney, Australia POSTCODE 2229

Website:

www.kineticsourcing.com.au

Email address:

sales@kineticsourcing.com.au

Phone no. *(if applicable):*

NZBN *(if applicable):*



Legal and trading name of the importer (if applicable):

ACM (NZ) Pty Limited

Address for service:

STREET NAME 47 Stonedon Drive

SUBURB East Tamaki

CITY, COUNTRY Auckland, New Zealand

POSTCODE 2013

Website:

www.acmhardware.com

Email address:

info@acmhardware.com

Phone no. (if applicable):

+64 9 320 4515

NZBN (if applicable):

9429030191990

Relevant Building Code

B2.3.1(b)
E2.3.1, E2.3.2, E2.3.7
F2.3.1

Statement on how the building product is expected to contribute to compliance:

B2 Durability

This product is a component within the plumbing services of a building, typically controlling the flow water at a terminus, is easy to access and replace, and failure would be easily detected during normal use.

E2—External moisture

The objective of this provision is to safeguard people from illness or injury that could result from external moisture entering the building.

F2 Hazardous Building Materials

This product is constructed of materials that will not emit harmful concentrations of substances from exposed surfaces.

- options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)
- standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured
- physical properties of the building product
- how the building product is intended to be used.

Limitations on the use of the building product:

<https://www.bunnings.co.nz/search/products?page=1&q=KINETIC+ROOFTITES&sort=BoostOrder>

EPDM Rubber material
Operating Temperature –45 to 140 degrees C
aluminum base for molding to the surface

Design requirements that would support the appropriate use of the building product:

<https://www.bunnings.co.nz/search/products?page=1&q=KINETIC+ROOFTITES&sort=BoostOrder>

Installation requirements (also provide link to the product installation guide):

Must be installed by a registered plumber and in accordance with AS/NZS3500.

<https://www.bunnings.co.nz/search/products?page=1&q=KINETIC+ROOFTITES&sort=BoostOrder>

Maintenance requirements (also provide link to the product maintenance guide):

None

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?:

Yes No

If yes, description of the warning or ban under section 26:

N/A

Date: 11/12/23